# Safety Data Sheet Prepared in Accordance with HCS 29 C.F.R. 1910.1200



## 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier INFRRNL-SDS Revision Date: 10/19/2022

Product Name: Supersedes Date: 07/11/2022

1.2 Relevant identified uses of the substance or mixture and uses

advised against

See Technical Datasheet. Construction chemical.

1.3 Details of the supplier of the safety data sheet

Supplier: FPT Infrastructure, Division of Fibrecrete Preservation

Technologies, Inc. 401 Old US 52 South Mount Airy, NC 27030

**USA** 

Phone: (336) 789 7259 Fax: (336) 789 7425 www.fptinfrastructure.com info@fptinfrastructure.com

Datasheet Produced by: EHS@FPTInfrastructure.com

1.4 Emergency telephone number: CHEMTREC +001 703 5273887 (Outside US)

CHEMTREC 1-800-424-9300 (Inside US)

Giftinformasjonen: +47 22 59 13 00

## 2. Hazard Identification

## 2.1 Classification of the substance or mixture

Serious Eye Damage, category 1 Flammable Liquid, category 2 STOT, single exposure, category 3, RTI Skin Irritation, category 2 Skin Sensitizer, category 1

## 2.2 Label elements

## Symbol(s) of Product



## Signal Word

Danger

## Named Chemicals on Label

Methyl methacrylate, Para-Toluidine Ethoxylated

## **HAZARD STATEMENTS**

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
PRECAUTION PHRASES		
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P235	Keep cool.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P403+233	Store in a well-ventilated place. Keep container tightly

## 2.3 Other hazards

No Information

## Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

## 3. Composition/Information On Ingredients

## 3.2 Mixtures

Hazardous ingredients

Name According to EEC	EINEC No.	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>	
Methyl methacrylate	201-297-1	80-62-6	75-100	H225-315-317-335	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1A, STOT SE 3 RTI

closed.

 Para-Toluidine
 103671-44-9
 2.5 - <10</th>
 H302-315-317-318-4
 Acute Tox. 4 Oral, Aquatic

 Ethoxylated
 12
 Chronic 3, Eye Dam. 1, Skin

Irrit. 2, Skin Sens. 1

CAS-No. M-Factors

80-62-6 0 103671-44-9 0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

## 4. First-aid Measures

## 4.1 Description of First Aid Measures

GENERAL NOTES: Show this safety data sheet to the doctor in attendance.

**AFTER INHALATION:** Remove person to fresh air. If signs/symptoms continue, get medical attention. Provide fresh air, rest and warmth. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin. AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

#### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

May cause sensitization by skin contact. Irritating to eyes, respiratory system and skin. May cause headache and dizziness. Acts as a defatting agent on skin.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11. When symptoms persist or in all cases of doubt seek medical advice.

## 5. Fire-fighting Measures

## 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

#### 5.2 Special hazards arising from the substance or mixture

Heating or fire conditions liberates toxic gas. Flash back possible over considerable distance. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

#### 5.3 Advice for firefighters

Fire will produce dense black smoke containing hazardous combustion products (see section 10). Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

## 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

## 6.3 Methods and material for containment and cleaning up

Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents.

## 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## 7. Handling and Storage

## 7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Open drum carefully as content may be under pressure. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used. PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid heat, sparks, flames and other ignition sources. Ultraviolet light. STORAGE CONDITIONS: Keep at temperatures between 5 and 25 °C. Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store away from: oxidising materials, acids, and alkalis. Store in upright position only. Storage of flammable liquids.

#### 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

## 8.1 Control parameters

Methyl methacrylate

## Ingredients with Occupational Exposure Limits (US)

Name CAS-No. ACGIH TWA ACGIH STEL ACGIH Ceiling

80-62-6

Para-Toluidine Ethoxylated 103671-44-9

Name CAS-No. OSHA PEL OSHA STEL

Methyl methacrylate 80-62-6 410 MGM3, 100

PPM

**50 PPM** 

100 PPM

Para-Toluidine Ethoxylated 103671-44-9

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

## 8.2 Exposure controls

#### **Personal Protection**

**RESPIRATORY PROTECTION:** Use compressed air or fresh air breathing apparatus in closed compartments. Wear respiratory protection with combination filter (dust and gas filter, EN 14387:2004+A1:2008) during spraying operations: Gas filter type A2 (organic substances). Dust filter P3 (for fine dust).

EYE PROTECTION: If splashes are likely to occur, wear: Face-shield, tightly fitting safety goggles (EN 166).

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber.

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties	9.1	Information on	basic physical	and chemical	properties
---	-----	----------------	----------------	--------------	------------

Appearance: Colorless

Physical State Liquid

**Odor** Characteristic

Odor threshold 0.05 ppm

**pH** Not determined

Melting point / freezing point (°C)

Not determined

Boiling point/range (°C) 101 - N.D.
Flash Point, (°F / °C) 12 C 54 F

Evaporation rate Slower than Ether

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive 2.1 - 12.5

limits - %(V)

Vapour Pressure< 1 mPa.s</th>Vapour density38.7 mbar

Relative density .94

Solubility in / Miscibility with water Not determined

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity

Not determined

Explosive properties

Not determined

Oxidising properties

Not determined

9.2 Other information

VOC Content g/l: Not determined

Specific Gravity (g/cm3) 0.940

## 10. Stability and Reactivity

#### 10.1 Reactivity

No reactivity hazards known under recommended storage and use conditions.

#### 10.2 Chemical stability

The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerise with heat evolution. Stable under recommended storage conditions.

## 10.3 Possibility of hazardous reactions

May polymerise in the presence of radical forming agents and reducing agents with evolution of heat.

#### 10.4 Conditions to avoid

Avoid heat, sparks, flames and other ignition sources. Ultraviolet light.

## 10.5 Incompatible materials

Strong oxidizing agents. Strong acids. Reducing agents. Avoid radical-forming starting agents, peroxides and reactive metals. Tertiary amines. Sulphur compounds.

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed. In case of fire hazardous decomposition products may be produced such as:Carbon monoxide (CO), carbon dioxide (CO2), oxides of nitrogen (NOx).

## 11. Toxicological Information

## 11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available.

Inhalation LC50: No information available.

Irritation: No information available.

Corrosivity: No information available.

**Sensitization:** No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

**Toxicity for reproduction:** No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
80-62-6	Methyl methacrylate	7872 mg/kg (oral. rat)	>5000 mg/kg	3750 ppm (inhalation, rat)	0.000	0.000

#### Additional Information:

Chronic exposure has been associated with various neurotoxic effects including permanent brain damage. Chronic exposure causes drying effect on the skin and eczema. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Gas or vapour is harmful on prolonged exposure or in high concentrations. Irritant of eyes and mucous membranes. CNS depressant. Inhalation is the main hazard in industrial use. The solvent vapours can be harmful and cause headaches, nausea, and intoxication. Acts as a defatting agent on skin.

## 12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):No informationIC50 72hr (Algae):No informationLC50 96hr (fish):No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

**12.4 Mobility in soil:** No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

**12.6 Other adverse effects:**No information

CAS-No.Chemical NameEC50 48hrIC50 72hrLC50 96hr80-62-6Methyl methacrylate720 mg/lNo information125.5 - 275.0 mg/l103671-44-9Para-Toluidine EthoxylatedNo informationNo informationNo information

## 13. Disposal Considerations

**13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

## 14. Transport Information

**14.1 UN number** UN1247

**14.2 UN proper shipping name** Methyl methacrylatem monomer, stabilized

Technical name Not applicable

14.3 Transport hazard class(es) 3

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5 Environmental hazards Not applicable
 14.6 Special precautions for user EmS-No.: Not applicable

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

## 15. Regulatory Information

## 15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

## U.S. Federal Regulations: As follows -

## **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

<u>Chemical Name</u> <u>CAS-No.</u> <u>%</u>

Methyl methacrylate 80-62-6 95

#### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

## U.S. Clean Air Act:

EPA Coating Category:

EPA VOC Content Limit (g/l):

Product VOC Content (g/l)

Thinning Recommendations:

Application Recommendations:

Not applicable

Not applicable

## U.S. State Regulations: As follows -

## New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

<sup>\*</sup> As per the federal EPA definition for coating categories in 40 CFR 59.401.

<sup>\*\*</sup> Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

## Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

## California Proposition 65:

No Proposition 65 Chemicals exist in this product.

## International Regulations: As follows -

#### \* Canadian DSL:

The following chemicals are listed on the NDSL; 103671-44-9 All other components of this product are listed on Canadian DSL or exempt.

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## 16. Other Information

## Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

#### Reasons for revision

Substance and/or Product Properties Changed in Section(s):
 01 - Identification
 11 - Toxicological Information

14 - Transportation Information

15 - Regulatory Information Revision Statement(s) Changed

This is a new Safety Data Sheet (SDS). .

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

## - Safety Data Sheet from raw material supplier

#### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation
GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit

STEL Short term exposure limit

STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.