

## Safety Data Sheet

Prepared in Accordance with HCS 29  
C.F.R. 1910.1200



### 1. Identification of the Substance/Mixture and the Company/Undertaking

- |  |   |                         |            |
|--|---|-------------------------|------------|
| <b>1.1 Product Identifier</b>  | 1500B5  | <b>Revision Date:</b>   | 01/07/2025 |
| <b>Product Name:</b>   | Fibrecrete Primer CP  | <b>Supersedes Date:</b> | 06/18/2024 |
| <b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b> | For use by appropriately trained applicators. Please see Technical Data Sheet. Advised against: others than recommended   |                         |            |
| <b>1.3 Details of the supplier of the safety data sheet</b>                              | <p><b>Supplier:</b> FPT Infrastructure, Division of Fibrecrete Preservation Technologies, Inc.<br/>401 Old US 52 South<br/>Mount Airy, NC 27030<br/>USA<br/>Phone: (336) 789 7259<br/>Fax: (336) 789 7425<br/>www.fptinfrastructure.com<br/>info@fptinfrastructure.com</p> <p><b>Datasheet Produced by:</b> EHS@FPTInfrastructure.com</p> |                         |            |
| <b>1.4 Emergency telephone number:</b>   | +1 703-741-5970 - North America<br>+1 800-424-9300<br>+55 11 4349 1359 - South America<br>+52 55 8526 4930 - Central America<br>+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa<br>+65 3163 8374 - Asia, South Asia, And Oceania   |                         |            |

### 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4  
 Eye Irritation, category 2A  
 Flammable Liquid, category 2  
 STOT, single exposure, category 3, NE

## 2.2 Label elements

### Symbol(s) of Product



### Signal Word

Danger

### Named Chemicals on Label

4-methylpentan-2-one, Ethyl acetate, Xylene

### HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.

### PRECAUTION PHRASES

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

## 2.3 Other hazards

No Information

### Results of PBT and vPvB assessment:

No information

## 3. Composition/Information On Ingredients

### 3.2 Mixtures

#### Hazardous ingredients

<u>Name According to EEC</u>	<u>EINEC No.</u>	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>	
Ethyl acetate	205-500-4	141-78-6	50 - <75	H225-319-336	Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE
4-methylpentan-2-one	203-550-1	108-10-1	10 - <25	H225-319-332-335	Acute Tox. 4 Inhalation, Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 RTI
Xylene	215-535-7	1330-20-7	2.5 - <10	H226-312-315-332	Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Flam. Liq. 3, Skin Irrit. 2

**CAS-No.**

141-78-6  
108-10-1  
1330-20-7

**M-Factors**

**Additional Information:** The text for GHS Hazard Statements shown above (if any) is given in Section 16.

**4. First-aid Measures****4.1 Description of First Aid Measures**

**GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice.

**AFTER INHALATION:** Move to fresh air. Consult a physician after significant exposure.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

**Self protection of the first aider:**

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**4.2 Most important symptoms and effects, both acute and delayed**

Harmful by inhalation. Irritating to eyes. Harmful in contact with skin and if swallowed.

**4.3 Indication of any immediate medical attention and special treatment needed**

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

**5. Fire-fighting Measures****5.1 Extinguishing Media:**

Carbon Dioxide, Dry Chemical, Foam

**FOR SAFETY REASONS NOT TO BE USED:** Alcohol, Alcohol based solutions, any other media not listed above.

**5.2 Special hazards arising from the substance or mixture**

Flammable.

**5.3 Advice for firefighters**

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**6. Accidental Release Measures****6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

**6.2 Environmental precautions**

Do not allow material to contaminate ground water system. Prevent product from entering drains.

**6.3 Methods and material for containment and cleaning up**

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

## 7. Handling and Storage

### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

**PROTECTION AND HYGIENE MEASURES:** Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Direct sources of heat.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

## 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>CAS-No.</u>	<u>ACGIH TWA</u>	<u>ACGIH STEL</u>	<u>ACGIH Ceiling</u>
Ethyl acetate	141-78-6	400 PPM		
4-methylpentan-2-one	108-10-1	20 PPM	75 PPM	
Xylene	1330-20-7	100 PPM	150 PPM	

<u>Name</u>	<u>CAS-No.</u>	<u>OSHA PEL</u>	<u>OSHA STEL</u>
Ethyl acetate	141-78-6	1400 MGM3, 400 PPM	
4-methylpentan-2-one	108-10-1	205 MGM3, 50 PPM	300 MGM3, 75 PPM
Xylene	1330-20-7	435 MGM3, 100 PPM	655 MGM3, 150 PPM

**FURTHER INFORMATION:** Refer to the regulatory exposure limits for the workforce enforced in each country.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** In case of insufficient ventilation wear suitable respiratory equipment.

**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses. Safety goggles.

**HAND PROTECTION:** Impervious gloves.

**Body Protection:** Long sleeved clothing.

Remove and wash contaminated clothing before re-use.

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance:	Colorless
Physical State	LIQUID
Odor	Strong MMA odor
Odor threshold	Not determined
pH	Non-aqueous
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	NOT DETERMINED - N.D.
Flash Point, (°F / °C)	52.7F / 11.5C
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits - %(V)	2.1 - 12.5
Vapour Pressure	@ 68F = 27mmHG (36mbar)
Vapour density	(where air = 1) 4.16
Relative density	Not determined
Solubility in / Miscibility with water	@68f = 16g/l
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	100-130mPa*s
Explosive properties	Not determined
Oxidising properties	Not applicable
<b>9.2 Other information</b>	
VOC Content g/l:	Not determined
Specific Gravity (g/cm <sup>3</sup> )	0.989

## 10. Stability and Reactivity

### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

### 10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Direct sources of heat.

**10.5 Incompatible materials**

Strong oxidizing agents.

**10.6 Hazardous decomposition products**Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.**11. Toxicological Information****11.1 Information on toxicological effects****Acute Toxicity:**

Oral LD50: No information

Inhalation LC50: No information

Irritation: No information available.

Corrosivity: Not corrosive to skin.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.

Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
141-78-6	Ethyl acetate	5600 mg/kg oral, rat		56000 mg/l/4h. (rat)	0.000	0.000
108-10-1	4-methylpentan-2-one	2080 mg/kg, oral, rat		5000 ppm / 1 hour, rat	0.000	0.000
1330-20-7	Xylene	3523 mg/kg, rat, oral	1,100 mg/kg, rabbit	5000 ppm/4 hrs rat, inhalation	5000ppm, Rat, 4hr	0.000

**Additional Information:**

No Information

## 12. Ecological Information

- 12.1 **Toxicity:**
- |                      |                |
|----------------------|----------------|
| EC50 48hr (Daphnia): | No information |
| IC50 72hr (Algae):   | No information |
| LC50 96hr (fish):    | No information |
- 12.2 **Persistence and degradability:** No information
- 12.3 **Bioaccumulative potential:** No information
- 12.4 **Mobility in soil:** No information
- 12.5 **Results of PBT and vPvB assessment:** No information
- 12.6 **Other adverse effects:** No information

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
141-78-6	Ethyl acetate	No information	No information	
108-10-1	4-methylpentan-2-one	No information	No information	
1330-20-7	Xylene	3.82 mg/l	No information	2.6 mg/l, rainbow trout

## 13. Disposal Considerations

- 13.1 **WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

- |   |                |
|---|----------------|
| 14.1 UN number  | UN1866         |
| 14.2 UN proper shipping name  | Resin Solution |
| Technical name  | Not applicable |
| 14.3 Transport hazard class(es)   | 3              |
| Subsidiary shipping hazard  | Not applicable |
| 14.4 Packing group  | II             |
| 14.5 Environmental hazards  | Not applicable |
| 14.6 Special precautions for user   | Not applicable |
| EmS-No.:  | F-E, S-E       |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code | Not applicable |

## 15. Regulatory Information

- 15.1 **Safety, health and environmental regulations/legislation for the substance or mixture:**

**U.S. Federal Regulations: As follows -****CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Acute Toxicity (any route of exposure), Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

**Sara Section 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>%</u>
Ethyl acetate	141-78-6	59.69
4-methylpentan-2-one	108-10-1	17.05
Xylene	1330-20-7	8.27
Ethylbenzene	100-41-4	0.35
Toluene	108-88-3	0.09
Benzene	71-43-2	0

**Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

**U.S. Clean Air Act:**

EPA Coating Category:	Industrial Maintenance Coating
EPA VOC Content Limit (g/l):	450
Product VOC Content (g/l)	65
Thinning Recommendations:	The coating is to be applied without thinning.
Application Recommendations:	For professional use only.

\* As per the federal EPA definition for coating categories in 40 CFR 59.401.

\*\* Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

**U.S. State Regulations: As follows -****New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
Styrene-Butadiene-Styrene Block Copolymer	9003-55-8
Petroleum Hydrocarbon Resin	063393-89-5



**Pennsylvania Right-To-Know**

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
Styrene-Butadiene-Styrene Block Copolymer	9003-55-8

**California Proposition 65:**

WARNING: Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

WARNING: Reproductive Toxicant -- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**International Regulations: As follows -****\* Canadian DSL:**

All chemical ingredients included on inventory or exempt.

**15.2 Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**16. Other Information****Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

**Reasons for revision**

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

09 - Physical and Chemical Properties

15 - Regulatory Information

Revision Statement(s) Changed

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects
IMO	International Maritime Organization
Note P:	The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$ .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.