

Patch Packs™ Flex

Cold Patch

Contained in a Flexible Mesh Pack

Product Description

Patch Packs Flex are fast and easy, all-weather emergency repair materials for potholes, spalls, and other pavement defects at least 1" deep. They are made from greater than 90% recycled aggregate, a non-volatile binder and environmentally friendly cold asphalt contained in non-woven polypropylene fabric packs. The proprietary asphalt binder is formulated to allow Patch Packs to expand and compress by vehicle load, creating a bond to the existing surface and sealing the top and edges.

Basic Uses

Patch Packs Flex are used to repair asphalt and reactive concrete defects 1" and deeper:

- Bridge decks
- Asphalt and concrete paved roads and highways
- Leveling pavement to manholes, drains and other fixtures
- Cart and other multi-use pathways
- Parking lots

Features and Benefits

- Flexible net packs allow material to migrate in odd-shaped or narrow defects
- Quick, easy, mess-free installation
- No equipment required
- Immediate traffic opening
- Eco-friendly product with no VOCs
- All-weather, all-season installation

Physical Properties*

Property	Value
Aggregate	Content

Blend

VOC Content	none	
ASTM D6927	Marshall Stability	2,500 N
ASTM D3203	Void	3-15%
ASTM D6927	Flow	20-40 (1/100 cm)
ASTM D6927	Residual Stability	> 75%

* The values shown are based on system testing under laboratory conditions. Different field application conditions or lab equipment configurations may result in system value variances.

Packaging

- Box: Average 18 Packs based on weight of 44 lbs, 0.96 cubic feet
- Pallet: 56 Boxes
- Truckload: 18 Pallets

Installation

Site Preparation

- Remove loose debris. Area to be repaired may be wet or dry.

Application

- Place Patch Packs Flex in the repair area, slightly overlapping and facing traffic. Packs may extend above the surface by ½" to 2" depending on the depth of the repair area.
- Open to traffic to initiate compaction.

Clean Up

- None.

Limitations/ Shelf Life

2 years when stored in a dry place in original, closed packaging. Do not stack other materials on boxes to prevent compression. Optimal storage temperature: 40 to 90 °F (5 to 32 °C).

Warranty

FPT Infrastructure warrants its Products to be free of defects in materials but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, FPT Infrastructure makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to FPT Infrastructure Products. FPT Infrastructure's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of FPT Infrastructure Products proven to be defective, and FPT Infrastructure shall not be liable for any loss or damage.

Please refer to our website at fptinfrastructure.com for the most up-to-date Product Data Sheets.

NOTE: All FPT Infrastructure Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.